

251 North Avenue West, 2nd Floor
Westfield, New Jersey 07090
Tel.: (908) 518-7700
Fax: (908) 518-7795

Mayer Fortkort & Williams, PC
Attorneys At Law

Fax

FAX RECEIVED

MAR 18 2003

TECHNOLOGY CENTER 2800

To: Art Unit 2874	From: Marjorie Scariati
Fax: 703-872-9318	Pages: 6
Phone:	Date: 3/18/03
Re: 10/039,245	CC:

☐ Urgent ☒ For Review ☐ Please Comment ☐ Please Reply ☐ Please Recycle

PRIVACY AND CONFIDENTIALITY NOTICE

The information contained in this communication is confidential and may be legally privileged. It is intended solely for the use of the individual or entity to whom it is addressed and others authorized to receive it. If you are not the intended recipient, you are hereby notified that any disclosure, copying, distribution or taking of any action in reliance on the contents of this information is strictly prohibited.

If you received this communication in error, please immediately notify us by a collect telephone call to the writer and return the original message and documents to us at the above address via the United States postal service.

RE: 10/039,245

PLEASE SEE ATTACHED PRELIMINARY AMENDMENT

#80
PRE Amended
4/30/03
am

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Yan Wang et al.

Serial No.: 10/039,245

Filed: 12/31/2001

Title: OPTICAL COMPONENTS HAVING REDUCED INSERTION LOSS

Art Unit: 2874

Examiner: Unassigned

Docket No.: 00-12

FAX RECEIVED

MAR 18 2003

TECHNOLOGY CENTER 2800

Box NON FEE Amendment
Assistant Commissioner for Patents
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Sir:

In regard to the above-identified application, please enter the following preliminary amendment and remarks:

IN THE SPECIFICATION

Please amend the specification as follows:

Please replace paragraphs 0028, 0029 with the following rewritten paragraphs:

[0028] Returning to FIG. 4, waveguiding segments 3301 ... 330n have progressively smaller widths as they approach output waveguides 316. For instance, in the embodiment of the invention shown in FIG. 4, waveguiding segment 3301 may have a width of about 18 microns whereas waveguiding segment 330n may have a width of about 2 microns. Moreover, the width of cladding regions 3401 ... 340n between adjacent waveguiding segments become progressively larger as they approach waveguides 316. For instance, if the width of the first cladding region 3401 is about 2 microns the width of cladding region 340n may be about 18 microns. In this